



- NOTES**
- 1.) UNITS MUST BE ATTACHED TO IN-PLANT COMPRESSED AIR SUPPLY FOR CLEANING MECHANISM TO FUNCTION (90 MAX PSIG CLEAN DRY AIR)
 - 2.) VALVES AND CONTROL TIMER SYSTEM OPERATE ON 120V, 50-Hz. POWER.
 - 3.) WELDED STEEL CONSTRUCTION OF 12 GA. MILD STEEL.
 - 4.) SOLID STATE PULSE CONTROL TIMER IN NEMA 4 ENCLOSURE
 - 5.) PAINTED INSIDE & OUT CRIMSON RED.

- SPECIFICATIONS**
- TOTAL CARTRIDGES: 8
 - TOTAL CARTRIDGES: 16
 - COMPRESSED AIR: 1.0 SCF @90 psi per sec.

TITLE
RP8-2 BOLT TIGHTENER
DETAIL

DMC NO. 1563
REV. 2

DATE 12-17-97
BY J.D.
CHKD BY DMC
NO. 11
SH. 3 OF 4

TOLERANCES UNLESS NOTED OTHERWISE
3 DEC. PLACES 1/16" - .001"
SCALE 1:3 = 10"
DATE 11/11/97

METAL FAB
METAL FABRICATING CO.
NEW VENTURA, CA 95758
NEW VENTURA, CA 95758