



- NOTES
- 1.) CONSULT MANUFACTURER REPRESENTATIVE FOR MOTOR BLOWER HEIGHT AND OTHER SPECIFICATIONS.
 - 2.) UNITS MUST BE ATTACHED TO IN-PLANT COMPRESSED AIR SUPPLY FOR CLEANING MECHANISM TO FUNCTION (90 MAX PSIG CLEAN DRY AIR)
 - 3.) VALVES AND CONTROL TIMER SYSTEM OPERATE ON 120V, 50-Hz. POWER.
 - 4.) WELDED STEEL CONSTRUCTION OF 12 GA. MILD STEEL ENCLASURE
 - 5.) SOLID STATE PULSE CONTROL TIMER IN NEMA 4 ENCLOSURE
 - 6.) PAINTED INSIDE & OUT CRIMSON RED.

SPECIFICATIONS
TOTAL VALVES 6
TOTAL CARTRIDGES 12
COMPRESSED AIR 1.0 SCF @90 psi per sec.

TITLE		TOLERANCES UNLESS OTHERWISE NOTED	
RP6-2 BOLT TOGETHER WITH BLOWER DETAIL		3 DEC. PLACES	1/32"
DWG. NO. 1564		SCALE	1/32"=1"
DATE	12-17-97	CHG. BY	MC
APP'D		CHKD BY	MC
		DATE	11
		SH. 1 OF 4	
DWG. NO. 1564		METAL FAB	