



- NOTES**
- 1.) UNITS MUST BE ATTACHED TO IN-PLANT COMPRESSED AIR SUPPLY FOR CLEANING MECHANISM TO FUNCTION (80 MAX psig CLEAN DRY AIR)
  - 2.) WELDED STEEL CONSTRUCTION OF 12 Ga. MILD STEEL.
  - 3.) FINISH: INDUSTRIAL GRADE CRIMSON RED INSIDE & OUT.
  - 4.) DUST TRAY CAPACITY: 1.75 CUBIC FT.
  - 5.) INLET COLLAR SIZES 6 IN. 8 IN.

**SPECIFICATIONS**  
 TOTAL VALVES, 1  
 TOTAL CARTRIDGES, 2  
 COMPRESSED AIR 1.0 SCF @80psi per sec.

<b>TITLE</b> RP2 SPECIFICATION				TOLERANCES UNLESS OTHERWISE SPECIFIED 3 DEC PLACES +/- .000 4 DEC PLACES +/- .001 ANGLES 1/2° FINISHES AS NOTED VICTORIA, BC CAN.		 METAL-FAB INDUSTRIAL FABRICATION VICTORIA, BC CAN.	
DWG. BY NC	DATE 2-2-98	CHKD. BY JJ	DWN. 11	SHEET NO. SH.1 OF 1	DWG. NO. L1582	REV. 1	