


# Ambient T-Style Air Cleaner MXT7000

**Specifications and Technical Data** 

#### TYPICAL APPLICATIONS:

Ambient Capture of Process Dusts / Mists Generated in Manufacturing processes:

- Welding Smoke & Fumes
- Grinding / Sanding / Polishing
- Metalworking / Composites
- Coolant / Oil Mist & Smoke
- Other Nuisance Dusts Generated in Industrial Processes



# **STANDARD FEATURES:**

- T-SHAPED DESIGN—DUAL INLET EACH END WITH SINGLE CENTER EXHAUST •
- 4" PLEATED PRE-FILTER
- Belt Driven Blower
- ADJUSTABLE 4-WAY EXHAUST GRILLE
- QUIET OPERATION 75 dBA
   AT 6' WITH SILENCER
- No Ducting Required
- CFM up to 7,550


# **OPTIONS:**

- HORIZONTAL OR VERTICAL CABINET
- 0-5" Magnehelic Gauge
- MERV 8 SCRIM PRE-FILTER ADDITIONAL "FILTER-SAVER" OPTION
- SILENCER
- MULTIPLE MOUNTING OPTIONS AVAILABLE
  - 1) EYEBOLTS
  - 2) C-CHANNEL
  - 3) WALL MOUNT-VERTICAL CONFIGURATION ONLY
  - 4) FLOOR STAND-VERTICAL CONFIGURA-TION ONLY

# **HOW IT WORKS:**

Contaminated air is drawn in from each end of the collector, and passes through the pleated pre-filters, effectively removing the larger particulate from the airstream.

Next the air passes through the primary filtration system, 8 pocket bag filters, where the smaller particles of airborne impurities are captured. Clean, pollution-free air is then discharged out the center exhaust grille providing a *Breathe Easy*, safe, work environment.



L3038-12/21

Toll-Free: 866-566-4276 Phone: 316-946-5875 Fax: 316-219-2995

# **MXT7000** MICRO AIR 30.00 C/C 3/8-16 UNC THREADED HOLES TYP. (4) PLACES ELECTRICAL JUNCTION BOX 0 43.63 C/C 47.25 3/8-16 UNC THREADED 72.00 30.00 HOLES TYP. (4) PLACES ELECTRICAL 25.19 0 O.A.H. 23.63 20.00 C/C HORIZONTAL STACK CONFIGURATION 48.81 47.25

#### VERTICAL STACK CONFIGURATION

### **MXT7000 SPECIFICATIONS:**

## **OVERALL DIMENSIONS:**

25" H X 48" W X 72" L NO SILENCER—HORIZONTAL
49" H X 24" W X 72" L NO SILENCER—VERTICAL
25" H X 72" W X 72" L W/ NON-LOUVERED SILENCER—HORIZ. .
49" H X 48" W X 72" L W/ NON-LOUVERED SILENCER—VERTICAL
25" H X 73" W X 72" L W/ LOUVERED SILENCER—HORIZONTAL.
49" H X 49" W X 72" L W/ LOUVERED SILENCER—VERTICAL

#### WEIGHT:

\*400 LBS ACTUAL WEIGHT
\*450 LBS SHIPPING WEIGHT
\*WEIGHT VARIES DEPENDING UPON
OPTIONS SELECTED

#### CABINET:

\*HEAVY DUTY 17 GA. WELDED GALVANEAL STEEL W/EXTERIOR SURFACES GROUND SMOOTH

\*OPTIONS FOR HORIZONTAL OR VERTICAL CONFIGURATION

#### FINISH:

INDUSTRIAL GRADE TEXTURED BAKED CRIMSON RED ENAMEL PAINT—INSIDE AND OUT

## **FILTRATION OPTIONS:**

FOUR EA. MERV 15, 24" X 24" X 22" 95% BAG FILTERS FOUR EA. MERV 10, 24" X 24" X 22" 55% BAG FILTERS

#### PREFILTER

FOUR EA. 24" X 24" X 4" PLEATED PREFILTER (STD.) TWO EA. MERV 8 SCRIM PRE-FILTER (OPTIONAL)

#### **FILTER ACCESS:**

FRONT LOAD, EACH END FOR EASY ACCESS

#### **NOISE LEVEL:**

90 dBA AT 6' AWAY FROM UNIT—NO SILENCER 75 dBA AT 6' AWAY FROM UNIT W/ NON-LOUVERED SILENCER 81 dBA AT 6' AWAY FROM UNIT W/ LOUVERED SILENCER

#### **INLET / EXHAUST:**

T-STYLE INTAKE AT EACH END / EXHAUST CENTER THROUGH 4 WAY ADJUSTABLE GRILLE

#### MOTOR:

5 HP, 1760 RPM, TEFC

#### **BLOWER:**

12-9 BELT DRIVEN, 1500 RPM

# **INPUT VOLTAGE:**

230/460 VAC, 60 Hz, 3-PHASE

# MAX CURRENT:

12.6 / 6.3 AMPS

#### AIR FLOW:

UP TO 7,550 CFM

# FILTER CHANGE INDICATOR (OPTIONAL):

0-5" MAGNEHELIC GAUGE

#### **MOUNTING OPTIONS:**

EYEBOLTS, C-CHANNEL, WALL MOUNT (VERTICAL ONLY), FLOOR STAND (VERTICAL ONLY)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

L3038-12/21